



SS22A THRU SS2DA

Surface Mount Schottky Barrier Rectifier

Features


- ★ Low profile package
- ★ Ideal for automated placement
- ★ Guardring for overvoltage protection
- ★ Low power losses, high efficiency
- ★ Low forward voltage drop
- ★ High surge current capability

Mechanical Data

- ★ Case: Molded plastic, SMA/DO-214AC
- ★ Epoxy: UL 94V-0 rate flame retardant
- ★ Terminals: Solderable per MIL-STD-750, method 2026
- ★ Polarity: Color band denotes cathode end
- ★ Mounting position: Any

Voltage Range 20 to 200V
Current 2.0 Ampere

SMA/DO-214AC



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

PARAMETER	SYMBOL	SS22A	SS23A	SS24A	SS25A	SS26A	SS28A	SS2BA	SS2CA	SS2DA	UNIT						
Maximum repetitive peak reverse voltage	V_{RRM}	20	30	40	50	60	80	100	150	200	V						
Maximum RMS voltage	V_{RMS}	14	21	28	35	42	56	70	105	140	V						
Maximum DC blocking voltage	V_{DC}	20	30	40	50	60	80	100	150	200	V						
Maximum average forward rectified current	$I_F(AV)$	2.0								A							
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	I_{FSM}	50								A							
Maximum instantaneous forward voltage @ $I_F=2.0A$	V_F	0.55		0.70		0.85		0.95		V							
Maximum DC reverse current @ $T_A=25^\circ C$ at rated DC blocking voltage @ $T_A=100^\circ C$	I_R	0.4 10								mA							
Typical thermal resistance (Note 1)	$R_{\theta JA}$	75								$^\circ C/W$							
	$R_{\theta JL}$	17								$^\circ C/W$							
Operating junction temperature range	T_J	-55 to +125				-55 to +150				$^\circ C$							
Storage temperature range	T_{STG}	-55 to +150								$^\circ C$							

NOTE : (1) PCB mounted with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas

RATINGS AND CHARACTERISTICS CURVES SS22A THRU SS2DA

Fig.1 - Forward Current Derating Curve




Fig.2 - Maximum Non-Repetitive Peak Forward Surge Current




Fig.3 - Typical Instantaneous Forward Characteristics




Fig.4 - Typical Reverse Leakage Characteristics

