



S3AB THRU S3MB

Surface Mount Standard Rectifier

Features


- ★ Low forward voltage drop
- ★ High current capability
- ★ Low reverse leakage current
- ★ High surge current capability

Mechanical Data

- ★ Case: Molded plastic, SMB/DO-214AA
- ★ Epoxy: UL 94V-0 rate flame retardant
- ★ Terminals: Solderable per MIL-STD-750, method 2026
- ★ Polarity: Color band denotes cathode end
- ★ Mounting position: Any

Voltage Range 50 to 1000 V
Current 3.0 Ampere

SMB/DO-214AA



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

PARAMETER	SYMBOL	S3AB	S3BB	S3DB	S3GB	S3JB	S3KB	S3MB	UNIT
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward rectified current @ $T_L=110^\circ\text{C}$	$I_{F(AV)}$	3.0							A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	I_{FSM}	100							A
Maximum instantaneous forward voltage @ $I_F=3.0\text{A}$	V_F	1.15							V
Maximum DC reverse current @ $T_A=25^\circ\text{C}$ at rated DC blocking voltage @ $T_A=125^\circ\text{C}$	I_R	10 250							μA
Typical junction capacitance (Note 1)	C_J	40							pF
Typical thermal resistance from junction to lead (Note 2)	$R_{\theta JL}$	10							$^\circ\text{C}/\text{W}$
Operating junction and storage temperature range	T_J, T_{STG}	-55 to +150							$^\circ\text{C}$

NOTES : (1) Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts DC.
 (2) Mounted on PCB with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas.

RATINGS AND CHARACTERISTICS CURVES S3AB THRU S3MB

Fig.1 - Forward Current Derating Curve




Fig.2 - Maximum Non-Repetitive Peak Forward Surge Current




Fig.3 - Typical Instantaneous Forward Characteristics




Fig.4 - Typical Reverse Leakage Characteristics




Fig.5 - Typical Junction Capacitance

